



1000-991GX

Gloss White Polymeric Calendered Vinyl With Gray Permanent Adhesive

Features

- ✓ 2.75mil gloss white polymeric calendered vinyl offering a cost-effective solution for indoor and outdoor graphic
- ✓ Gray permanent adhesive creating good opacity
- ✓ Liner with air egress eliminating easily wrinkle and bubble
- ✓ Reliable durability and performance
- ✓ Compatible with cold laminating film 200-000/200-002/200-005

Face Film

70um gloss white polymeric calendered vinyl

Adhesive

gray permanent solvent-based acrylic

Release Liner

100g double-PE Liner with air egress

Durability

up to 5 years (unprinted)

Compatible Ink

solvent, eco-solvent, latex, UV

Size

54" / 60" * 150ft

Application

- ✓ Indoor and outdoor signage / advertising
- ✓ Point of purchase / retail
- ✓ Exhibition graphics
- ✓ Vehicle graphics (flat or simple curved surfaces)

Shelf Life & Storage Condition

- ✓ Stored at 25°C (77°F) and 50% relative humidity
- ✓ 2 years in original packaging



1000-991GX

Gloss White Polymeric Calendered Vinyl With Gray Permanent Adhesive

Physical Characteristics

Face Film

Film Type	Gloss White Polymeric Calendered Vinyl
Film Thickness	2.75mil / 70um \pm 5%
Gloss(60%)	80
Dimensional Stability	< 1.0 mm

Adhesive

Adhesive Type	Gray Permanent Solvent-based Acrylic
Adhesive Thickness	30um
Peel Strength (N/25mm) 20 min	12 N/25mm
Peel Strength (N/25mm) 24 hrs	15 N/25mm
Cohesion	Pass

Liner

Liner Type	White Double-PE Coated with Air Egress
Liner Weight (gsm)	100g

Other Features

Temperature for Application	Min +10°C
Shelf Life	2 years
Storage Temp / Rel. Humidity	25°C (77°F) / 50%
Durability	Up to 5 years
Flammability	Pass