



200-180

Gloss Clear Polymeric Calendered Vinyl With Clear Permanent Adhesive

Features

- ✓ 2.75mil gloss clear polymeric calendered vinyl offering a cost-effective solution
- ✓ Protecting image from scratches
- ✓ Reliable durability and performance
- ✓ Compatible with Graphictac 1000 series digital printing media:

Face Film

70um gloss clear
polymeric calendered
vinyl

Adhesive

clear permanent
solvent-based acrylic

Release Liner

80g single-PE liner

Durability

up to 4 years

Size

54" / 60" * 150ft

Application

- ✓ Indoor and outdoor signage / advertising
- ✓ Point of purchase
- ✓ Window graphics
- ✓ Fleet / Vehicle (only flat or simple curved surfaces)
- ✓ Backlit

Shelf Life & Storage Condition

- ✓ Stored at 25°C(77°F) and 50% relative humidity
- ✓ 2 years in original packaging



200-180

Gloss Clear Polymeric Calendered Vinyl With Clear Permanent Adhesive

Physical Characteristics

Face Film

| | |
|-----------------------|--|
| Film Type | Gloss Clear Polymeric Calendered Vinyl |
| Film Thickness | 2.75mil / 70um \pm 5% |
| Gloss(60%) | 102 \pm 5% |
| Dimensional Stability | Less than 2mm |

Adhesive

| | |
|-------------------------------|---------------------------------------|
| Adhesive Type | Clear Permanent Solvent-based Acrylic |
| Adhesive Thickness | 25 um |
| Peel Strength (N/25mm) 20 min | 12 N/25mm |
| Peel Strength (N/25mm) 24 hrs | 14 N/25mm |
| Cohesion | Pass |

Liner

| | |
|--------------------|---------------------------------------|
| Liner Type | White Single-PE Coated Silicone Paper |
| Liner Weight (gsm) | 80g |

Other Features

| | |
|------------------------------|------------------|
| Temperature for Application | Min +10°C |
| Shelf Life | 2 years |
| Storage Temp / Rel. Humidity | 25°C(77°F) / 50% |
| Durability | Up to 4 years |
| Flammability | Pass |