



50-W01

White Static Cling Vinyl

Features

- ✓ High gloss finish
- ✓ Applies without adhesive
- ✓ Dimensionally stable liner for easy converting
- ✓ Reliable durability and performance

Face Film

150um high gloss white
static cling vinyl

Adhesive

No adhesive

Liner

140g single thickened
PE coated paper

Durability

2 years (indoor)
6 months (outdoor)

Compatible Ink

solvent, eco-solvent,
latex, UV, screen

Size

42" / 50" / 54"

Application

- ✓ Indoor signage
- ✓ Outdoor signage (short term durability)
- ✓ Point of purchase window decals
- ✓ Automotive window decals
- ✓ Reusable seasonal decal

Application Techniques

- ✓ Flat, smooth and clean surface
- ✓ Surface's temperature close to room temperature
- ✓ Suitable for wet apply / dry apply



50-W01
White Static Cling Vinyl

Physical Characteristics

Face Film

Film Type	High Gloss White Static Cling Vinyl
Film Thickness	5.9mil / 150um \pm 5%
Gloss(60%)	\geq 95
Dimensional Stability	< 2.0 mm

Liner

Liner Type	White Single Thickened PE Coated Paper
Liner Thickness	7.9mil / 200um \pm 5%
Liner Weight (gsm)	140g

Other Features

Temperature for Application	10°C to 40°C (50°F to 104°F)
Shelf Life	1 years
Storage Temp / Rel. Humidity	25°C (77°F) / 50%
Durability	2 years (indoor) 6 months (outdoor)

***Rain, wind and temperature may limit the bond of static vinyl to exterior windows.